

JHA-P42104BMHX Series

7-port Full Gigabit PoE Switch , 4*10/100/1000M PoE ports and 1*10/100/1000M uplink RJ45 port and 2*10/100/1000M SFP Port



Features

- **Full gigabit rate, dual RJ45 ports uplink**
 - ◇ Provides Gigabit Ethernet ports and dual RJ45 ports uplink for flexible networking and meets the networking requirements of various scenarios.
 - ◇ All ports support non-blocking wire-speed forwarding for smoother transmission.
 - ◇ Support IEEE 802.3x full-duplex flow control and Backpressure half-duplex flow control.
- **Intelligent PoE power supply**
 - ◇ 4*10/100/1000Base-T RJ45 ports, meeting the needs of security monitoring, teleconferencing system, wireless coverage, and other scenarios.
 - ◇ 1*10/100/1000Mbps RJ45 port is provided to meet the seamless connection to the Gigabit network.

- ◇ 2 10/100/1000Mbps SFP fiber optic module expansion slot ports, and use SFP fiber optic modules together.
- ◇ IEEE802.3af/at PoE standard, without damaging non-PoE devices.
- ◇ Priority system for PoE port, it will supply power to the high priority level port first when the power budget is insufficient and avoid overwork of the device.

■ **Stable and reliable, easy to use**

- ◇ CCC,CE, FCC, RoHS.
- ◇ Plug and play, no configuration, simple and convenient.
- ◇ Low power consumption, galvanized steel casing, no fan.
- ◇ The user-friendly panel can show the device status through the LED indicator of PWR, Link, PoE.
- ◇ Self-developed power supply, high redundancy design, providing a long term and stable PoE power output.

Introduction


The JHA-P42104BMHX is a full gigabit unmanaged PoE switch. it has 4*10/100/1000Base-T PoE ports and 1*10/100/1000Base-T uplink RJ45 ports and 2*1000M SFP slot, Port 1-4 can support IEEE802.3af/at standard PoE power supply. Single-port PoE power up to 30W. As a PoE power supply device, it can automatically detect and recognize the power receiving equipment that meets the standard and supply power through the network cable. It can supply power to POE terminal equipment such as wireless AP, webcam, VoIP phone, video access control intercom, etc. through network cable to meet the network environment that needs high-density PoE power supply. It is suitable for hotels, campuses, factory quarters and small and medium-sized enterprises to form an economy efficient network. Unmanaged model, plug and play, no configuration, easy to use.

Specification

Model	JHA-P42104BMHX
Interface Characteristics	
Fixed Port	4*10/100/1000Base-T PoE ports (Data/Power) 1*10/100/1000Base-T uplink RJ45 ports (Data) 2*1000Base-X uplink SFP ports (Data)
Ethernet Port	10/100/1000Base-T auto detect, full / half duplex MDI / MDI-X adaptive
Twisted Pair Transmission	10BASE-T:Cat3,4,5 UTP(≤100 meter) 100BASE-TX:Cat5 or later UTP(≤100 meter) 1000BASE-T : Cat5e or later UTP(≤100 meter)
Chip Parameter	
Network Protocol	IEEE802.3 10BASE-T, IEEE802.3i 10Base-T IEEE802.3u 100Base-TX, IEEE802.3ab 1000Base-T, IEEE802.3x
Forwarding Mode	Store and Forward(Full Wire Speed)
Switching Capacity	22Gbps (Non-blocking)
Forwarding Rate@64byte	8.93Mpps
MAC	2K
Buffer Memory	2M
Jumbo Frame	1536byte
LED Indicator	Each port has 1 LINK/ACT. VLAN POE Status indicator Overall power indicator
PoE & Power Supply	
PoE Port	Port 1 to 4
Power Supply Pin	Default 1/2(+), 3/6(-)
Max Power Per Port	30W, IEEE802.3af/at
Total PWR / Input Voltage	65W/ (AC100-240V)

Power Consumption	Standby <5W, Full load <65W
Power Supply	Built-in power supply, AC100~240V 50-60Hz 1.1A
Physical Parameter	
Operation TEMP / Humidity	-20~+55°C, 5%~90% RH Non condensing
Storage TEMP / Humidity	-40~+75°C, 5%~95% RH Non condensing
Dimension (L*W*H)	202*140*45mm
Net /Gross Weight	<1.03kg / <1.5kg
Installation	Desktop, wall-mounted
Certification & Warranty	
Lightning Protection	Lightning protection: 4KV 8/20us, Protection level: IP30
Certification	CCC, CE mark, commercial, CE/LVD EN60950, FCC Part 15 Class B, RoHS
Warranty	1 year, lifelong maintenance.
DIP Switch Descriptions:(4 optional functions)	
1.10M;	6.Jumbo Frame
2.VLAN(Port VLAN or Tag VLAN)	7.EEE Power
3.QinQ	8.RSTP
4.SFP port SPEED(1G or 2.5G)	9.QoS
5.Flow Control	10.PD reboot

Dimension



Ordering Information

Model	Description
JHA-P42104BM HX	Unmanaged PoE switch, 4*10/100/1000M PoE ports+1*10/100/1000M RJ45 ports+2*1000M uplink SFP ports. built-in 65W power supply, support IEEE802.3af/at PoE standard, with 4 DIP Switch

Packing List

	CONTENT	QTY	UNIT
Packing List	7-port full gigabit PoE switch	1	SET
	AC Power Line	1	PC
	User Guide	1	PC
	Warranty Card	1	PC