

## 4\*E1 over Ethernet(IP)

### DeskTop Type

#### Overview

TDMoIP-4E1 is mainly used to transmit voice signal over IP network. It has 4E1 interface, 2 UTP Ethernet port and 1\*fiber Ethernet port. TDMoIP-1E can connect TDM device and user's low cost wireless or lineate Ethernet/IP configuration, without affecting the voice quantity. assures connecting to physical E1 interface of any device seamlessly, such as PBX, mobile base station, SS7 signaling device and voice mail system. It can be used in the communication system based on E1, such as LAN, WAN, MAN and wireless network.

Providing emulation E1 channel through Ethernet, the difficulty is rebuilding timing information of E1 code stream effectively at the exit of network. The special disadvantages of Ethernet itself, such as random packet delay, without effective timing transmit mechanism, transmission error or collision that brings on packet lose, must be conquered. Our company resolves the difficulties above faultlessly through availing ourselves of technical advantage and adapting advanced clock disposal technology. TDMoIP-4E encapsulates the date of E1 code stream to the packet and transmits it to the remote device through Ethernet.

#### Photos



Desktop type

#### Features

- Provide 1-4 E1 channels interface transparently, confirming to ITU-G.703.
- High transmit efficiency, low transmit delay.
- Provide 4\*E1 channels and 2\*10/100/1000Base-TX and 1\*1000Base-FX interface.
- The length of Ethernet packet can be set, supporting huge packet.
- User can select IP protocol encapsulation or simplicity Ethernet type.
- Support VLAN setting.
- Support Ethernet ping function.
- Support package loss indicator function for E1 transmission line.
- Local and remote E1 loop and local E1 enable function.
- Point to point or point to multi-points connections, satisfying different applications.
- High efficiency transmission, up to 90% bandwidth utility ratio.
- Support two type interfaces-75Ω and 120Ω-unneed setting.
- 10/100M Ethernet, full/half duplex auto-adapt, support auto-MDIX.

- When selecting network adaptation clock, it can resume the original clock accurately through TDM clock resumption mechanism, stable clock, little jitter and small excursion, conforming to ITU-T clock jitter and excursion standard.
- The device Support WEB management platform, online software upgrades, the host side can manage the work of each state machine equipment;

## Parameters

### Ethernet interface(10/100/1000M)

Interface rate: 10/100/1000 Mbps, half/full duplex auto-negotiation  
 Interface Standard: Compatible with IEEE 802.3, IEEE 802.1Q (VLAN)  
 MAC Address Capability: 4096  
 Connector: RJ45, support Auto-MDIX

### E1 Interface

Standard: conform to G.703 standard  
 Code rate: 2.048Mbit/s±50ppm  
 Code type: HDB3  
 Impedence: 75Ω ( unbalance ) / 120 ( balance )  
 Connector: BNC ( unbalance ) / RJ45 ( balance )  
 Jitter tolerance: conform to G.742 and G.823

### Working environment

Working temperature: -10°C ~ 50°C  
 Working Humidity: 5%~95 % (no condensation)  
 Storage temperature: -40°C ~ 80°C  
 Storage Humidity: 5%~95 % (no condensation)

## Specifications

Model	JHA-T-4E1
Functional Description	4*E1 over Ethernet ,Internal power AC220V/DC48V/DC24V can be optional
Power	Power supply: AC180V ~ 260V ; DC -48V ; DC +24V Power consumption: ≤10W
Dimension	216X130X31mm(WXDXH)
Weight	1.3KG

## Application

